



NeoSapphire

NS3611 All-Flash Array

- Superior performance with 360K IOPS for 4KB random write in a compact 1U form factor
- High density and huge capacity with 20 SSDs offering 11TB usable capacity
- Dual-port Fibre Channel interface for easy integration with SAN environment
- Thin provisioning and zero-page deduplication for flexible capacity management




NeoSapphire All-Flash Array Series - NS3611
SPECIFICATIONS

Form Factor	1U rack mount
IOPS for 4KB Random Write	360K sustained
Flash Management	FlexiRemap technology
Usable Capacity ¹	11TB
Number of SSD	20 x hot-swappable SSD
Flash Type	MLC
Connectivity	2 x 16G Fibre Channel LC SFP+
Storage Protocol	Fibre Channel
Management Interface	Web-based management interface (via HTTP/HTTPS) CLI (via serial port)
Power Supply	400W 1+1 redundant
Feature Highlight	Optimized low-latency performance for SANs High density with 20 drives in 1U rack space Data protection through redundancy
Environmental Temperature	Operating: 10°C to 35°C Storage (non-operating): -20°C to 60°C
Environmental Humidity	Operating: 10% to 90% non-condensing Storage (non-operating): 5% to 95% non-condensing

¹ Usable capacity refers to the approximation of the storage capacity that users can have. The accurate usable capacity may vary depending on software configurations and other factors.

©2015-2016. All rights reserved. AccelStor, Inc. AccelStor, FlexiRemap, and NeoSapphire are trademarks or registered trademarks of AccelStor, Inc. in the United States of America and/or other countries. Other names and brands may be claimed as the property of others. Pictures are not contractual.

In a continuing effort to improve the quality of our products, information in this brochure is subject to change without notice. Images appearing are only representations of some of the configurations available. Availability may vary depending on region.

AccelStor, Inc. reserves the right to the interpretation of the above specifications, terms and conditions.