










**SANS**  
**DIGITAL**







SERIES	MOBILESTOR	TOWERSTOR	MOBILERAID	
MODEL	MS1CT+ / MS1UT+B	TS1CT / TS1UT+B	MR2UT+ / MR2UT+B	MR2CT+
PHOTO				
FORM FACTOR	1-Bay Tower	1-Bay Tower	2-Bay Tower	
HARD DRIVE TRAYS	Hot-Swappable 3.5" x1	3.5" SATA Hard Drive	Hot-Swappable 3.5" x 2	
MAXIMUM CAPACITY	4TB	4TB	8TB	
DRIVE INTERFACE	SATA	SATA	SATA	
HOST INTERFACE	USB 3.0 & eSATA (MS1UT+B) / USB 3.0, eSATA, 1394b (MS1CT+)	USB 3.0 & eSATA (TS1UT+B) / USB 3.0, eSATA, 1394b (TS1CT+)	USB 3.0 x1 & eSATA x1	USB 3.0 x1, eSATA x1, 1394b x2
RAID LEVEL	N/A	N/A	0, 1, Spanning & JBOD	
EXPANSION PORTS	N/A	N/A	N/A	
HOT-SPARE	N/A	N/A	N/A	
COOLING FAN	N/A	N/A	1.6" Ball Bearing	
HEAT SINK	N/A	N/A	N/A	
POWER SUPPLY	24W Power Adapter	24W Power Adapter	60W Power Adapter	
SUPPORTED OS	Windows / MAC / Linux	Windows / MAC / Linux	Windows / MAC / Linux	
STATUS INDICATORS	Hard Drive & Power LEDs	Hard Drive & Power LEDs	Fan, Temperature, Power, HDD LEDs	
DIMENSIONS (IN)	1.6(W) x 8.5(D) x 3.5(H)	1.4(W) x 8.5(D) x 4.5(H)	4.8(W) x 8.0(D) x 4.0(H)	
WEIGHT (LB)	2.5	2.5	3.8	
SAFETY REGULATIONS	CE, FCC, UL, RoHS	CE, FCC, UL, RoHS	CE, FCC, UL, RoHS	
LIMITED WARRANTY	1 Year	1 Year	1 Year	





SERIES	MOBILERAID	MOBILESTOR		
MODEL	MR2U+ / MR2U+B	MS4UM+ / MS4UM+B	MS4UT+ / MS4UT+B	MS4CT+
PHOTO				
FORM FACTOR	2-Bay Tower	4-Bay Tower		
HARD DRIVE TRAYS	Hot-Swappable 3.5" x2	Hot-Swappable 3.5" x4		
MAXIMUM CAPACITY	8TB	16TB		
DRIVE INTERFACE	SATA	SATA		
HOST INTERFACE	USB 3.0 x2	USB 3.0 x1 & eSATA(PM) x1	USB 3.0 x1 & eSATA x1	USB 3.0 x1, eSATA x1, 1394a/b
RAID LEVEL	JBOD	JBOD	0, 1, 3, 5, 1+0, Spanning	
EXPANSION PORTS	N/A	N/A		
HOT-SPARE	N/A	N/A	Yes	
AUTO REBUILDING	N/A	N/A	Yes	
COOLING FAN	1.6" Ball Bearing	3" Ball Bearing Fan		
POWER SUPPLY	60W Power Adapter	60W (100V-240V)		
CONTROL INTERFACE	On / Off Switch Located on Back Panel	On / Off Button	RAID Selection Button	
STATUS INDICATORS	Fan, Temperature, Power, HDD LEDs	Fan, Hard drives status, Power LEDs		
DIMENSIONS (IN)	4.8(W) x 8.0(D) x 4.0(H)	5.3(W) x 9.7(D) x 7.0(H)		
WEIGHT (LB)	3.8	4.5		
SAFETY REGULATIONS	CE, FCC, UL, RoHS	CE, FCC, UL, RoHS		
LIMITED WARRANTY	1 Year	1 Year		





THUNDERBOLT SOLUTIONS	MOBILESTOR	TOWERRAID+		ELITERAID
MODEL	MS2TB+	TR4TB+	TR8TB+	ER104TB+ / ER208TB+
PHOTO				
FORM FACTOR	2-Bay Tower	4-Bay Tower	8-Bay Tower	1U 4-Bay / 2U 8-Bay
HARD DRIVE TRAYS	Hot-Swappable 3.5" x2	Trayless	Hot-Swappable 3.5" x8	Hot-Swappable 3.5" x4 / x8
MAXIMUM CAPACITY	8TB	16TB	24TB	16TB / 32TB
DRIVE INTERFACE	4 x 3.5" SATA	4 x 3.5" SATA	4 x 3.5" / 2.5" SATA	4 x 3.5" SATA / 8 x 3.5" SATA
HOST INTERFACE	Thunderbolt	Thunderbolt		Thunderbolt
RAID LEVEL	0, 1, JBOD	0, 1, 10, 5, JBOD		0, 1, 10, 5, JBOD
EXPANSION PORTS	N/A	N/A		N/A
HOT-SPARE	N/A	Yes		Yes
AUTO REBUILDING	Yes	Yes		Yes
COOLING FAN	1.6" Ball Bearing	3.15" Ball Bearing	4.7" Ball Bearing	1.6" x3 / 3" x2
POWER SUPPLY	60W (100-240V) Adapter	60W (100-240V) Adapter		150W / 460W(100V-240V)
CONTROL INTERFACE	WEB GUI	WEB GUI		WEB GUI
STATUS INDICATORS	Hard Drives Status & Power LEDs	Hard Drives Status & Power LEDs		Cooling Fan Status, Hard Drives & Power LED
DIMENSIONS (IN)	4.8(W) x 8.0(D) x 4.0(H)	5.3(W) x 10.0(D) x 7.1(H)	5.9(W) x 13.4(D) x 13.4(H)	19.0(W) x 15.0(D) x 1.7(H) 19.0(W) x 23.0(D) x 3.5(H)
WEIGHT (LB)	3.8	5.9	13	16.0 / 35.0
SAFETY REGULATIONS	CE, FCC, UL, RoHS	CE, FCC, UL, RoHS		CE, FCC, UL, RoHS
LIMITED WARRANTY	1 Year	1 Year		3 Years

2.5" SOLUTIONS	MOBILESTOR	ACCUSTOR	ELITESTOR	
MODEL	MS28X	AS108X	ES108X+B / ES108X6+B	ES224X6+B
PHOTO				
FORM FACTOR	8-Bay Tower	1U 8-Bay Rackmount	1U 8-Bay Rackmount	2U Rackmount
HARD DRIVE TRAYS	Hot-Swappable 2.5" x8	Hot-Swappable 2.5" x8	Hot-Swappable 2.5" x8	Hot-Swappable 2.5" x24
MAXIMUM CAPACITY	8TB	8TB	8TB	24TB
DRIVE INTERFACE	SAS / SATA	SAS / SATA	SATA	SAS / SATA
HOST INTERFACE	Mini-SAS x2	Mini-SAS x2	Mini-SAS x2 / SAS Expander x2	SAS Expander x2
RAID LEVEL	JBOD	JBOD	JBOD	
EXPANSION PORTS	N/A	N/A		N/A
HOT-SPARE	Supported via RAID Controller	Supported via RAID Controller	Supported via RAID Controller	
AUTO REBUILDING	Supported via Controller	Supported via Controller	Supported via Controller	
COOLING FAN	3" Ball Bearing x2	1.6" Ball Bearing x3	1.5" Ball Bearing x2	3" Ball Bearing x2
POWER SUPPLY	150W (100V-240V)	200W (100V-240V)	200W (100V-240V)	460W
CONTROL INTERFACE	Via RAID Controller	Via RAID Controller	Via RAID Controller	
STATUS INDICATORS	HDD Status & Power LEDs	HDD Status & Power LEDs	HDD Status & Power LEDs	Hard Drive & Failure LEDs
DIMENSIONS (IN)	7.0(W) x 10.5(D) x 5.5(H)	19.0(W) x 17.0(D) x 1.7(H)	19.0(W) x 18.0(D) x 1.7(H)	19.0(W) x 23.0(D) x 3.5(H)
WEIGHT (LB)	9.0	15.0	14.0	35.0
SAFETY REGULATIONS	CE, FCC, UL, RoHS	CE, FCC, UL, RoHS	CE, FCC, UL, RoHS	
LIMITED WARRANTY	1 Year	1 Year	3 Year	

Hardware RAID product available for SAS, iSCSI, and USB / eSATA

SERIES	ELITESTOR			
MODEL	ES104X+ / ES104X+B	ES208X6+B	ES316X6+B	ES424X6+B
PHOTO				
FORM FACTOR	1U 4-Bay Rackmount	2U 8-Bay Rackmount	3U 16-Bay Rackmount	4U 24-Bay Rackmount
HARD DRIVE TRAYS	Hot-Swappable 3.5" x4	Hot-Swappable 3.5" x8	Hot-Swappable 3.5" x16	Hot-Swappable 3.5" x24
MAXIMUM CAPACITY	16TB	32TB	64TB	96TB
DRIVE INTERFACE	SAS / SATA			
HOST INTERFACE	Mini-SAS	Mini-SAS 6G (SAS Expander)	Mini-SAS 6G (SAS Expander)	Mini-SAS 6G (SAS Expander)
RAID LEVEL	JBOD (RAID Supported Via RAID Controller)			
EXPANSION PORTS	N/A	Mini-SAS	Mini-SAS	Mini-SAS
HOT-SPARE	Supported via RAID Controller			
AUTO REBUILDING	Supported via RAID Controller			
COOLING FAN	1.6" Ball Bearing x3, 1.5" Power Supply Cooling Fan x1	3" Cooling Fan x2, 1.5" Power Supply Cooling Fan x1	4" Cooling Fan x2, 1.5" Power Supply Cooling Fan x3	4" Cooling fan x2, 1.5" Power Supply Cooling Fan x3
POWER SUPPLY	150W (100V-240V)	450W (100V-240V)	650W 2+1 Redundant	650W 2+1 Redundant
CONTROL INTERFACE	Via Additional RAID Controller			
STATUS INDICATORS	Fan, Temperature, Power, HDD LEDs			
DIMENSIONS (IN)	19.0(W) x 15.0(D) x 1.7(H)	19.0(W) x 23.0(D) x 3.5(H)	19.0(W) x 23.0(D) x 5.5(H)	19.0(W) x 23.0(D) x 7.0(H)
WEIGHT (LB)	18.0	35.0	46.0	54.0
SAFETY REGULATIONS	CE, FCC, UL, RoHS			
LIMITED WARRANTY	3 Years			





SERIES	ELITERAID			
MODEL	ER104UT+ / ER104UT+B	ER208UT+B	ER316UT+B	ER316I+B
PHOTO				
FORM FACTOR	1U 4-Bay Rackmount	2U 8-Bay Rackmount	3U 16-Bay Rackmount	3U 16-Bay Rackmount
HARD DRIVE TRAYS	Hot-Swappable 3.5" x4	Hot-Swappable 3.5" x8	Hot-Swappable 3.5" x16	Hot-Swappable 3.5" x16
MAXIMUM CAPACITY	16TB	32TB	64TB	64TB
DRIVE INTERFACE	SATA			
HOST INTERFACE	USB 3.0 x1 & eSATA x1	USB 2.0 x1 & eSATA x2	USB 2.0 x1 & eSATA x2	GbE x4 (SCSI)
RAID LEVEL	0, 1, 1+0, 5, Clone, JBOD	0, 1, 1+0, 3, 5, 6, JBOD	0, 1, 1+0, 3, 5, 6, JBOD	0, 1, 0+1, 3, 5, 6, 10, 30, 50, 60, JBOD
EXPANSION PORTS	N/A			
HOT-SPARE	Yes			
AUTO REBUILDING	Yes			
COOLING FAN	1.6" Ball Bearing x4, 1.5" Power Supply Fan x1	3" Ball Bearing x2, 1.5" Power Supply Fan x1	4" Cooling Fan x2, 1.5" Power Supply Cooling Fan x3	4" Cooling Fan x2, 1.5" Power Supply Cooling Fan x3
POWER SUPPLY	150W (100V-240V)	450W (100V-240V)	650W 2+1 Redundant	650W 2+1 Redundant
CONTROL INTERFACE	RAID Switch Monitoring Software	Web-based management, Serial Port or LCD	Web-based management, Serial Port or LCD	Web-based management, Serial Port
STATUS INDICATORS	Fan, Temperature, Power, HDD LEDs			
DIMENSIONS (IN)	19.0(W) x 15.0(D) x 1.7(H)	19.0(W) x 23.0(D) x 3.5(H)	19.0(W) x 23.0(D) x 5.5(H)	19.0(W) x 23.0(D) x 5.5(H)
WEIGHT (LB)	18.0	42.0	46.0	46.0
SAFETY REGULATIONS	CE, FCC, UL, RoHS			
LIMITED WARRANTY	3 Years			




ISCSI SOLUTIONS		ELITERAID		ACCURAIID	
MODEL	ER104I+ / ER104I+B	ER208I+B	AR316I / AR316IR	AR424I / AR424IR	
PHOTO					
FORM FACTOR	1U 4-Bay Rackmount	2U 8-Bay Rackmount	3U 16-Bay Rackmount	4U 24-Bay Rackmount	
HARD DRIVE TRAYS	Hot-Swappable 3.5" x4	Hot-Swappable 3.5" x8	Hot-Swappable 3.5" x16	Hot-Swappable 3.5" x24	
MAXIMUM CAPACITY	16TB	32TB	64TB	96TB	
DRIVE INTERFACE	SATA I / SATA II / SATA III		SAS / SATA		
HOST INTERFACE	Gigabit Ethernet x2 (iSCSI)		GbE x4 (iSCSI) (AR316I) / GbE x8 (iSCSI) (AR316IR)	GbE x4 (iSCSI) (AR424I) / GbE x8 (iSCSI) (AR424IR)	
RAID LEVEL	0, 1, 0+1, 3, 5, 6, 10, 30, 50, 60, JBOD		0, 1, 0+1, 3, 5, 6, 10, 30, 50, 60, JBOD		
EXPANSION PORTS	N/A		Mini-SAS (Up to 3 JBOD Units)		
AUTO REBUILDING	Yes		Yes		
REDUNDANT CONTROLLER	N/A		Single Upgradable (AR316I) / Redundant Controller (AR316IR)	Single Upgradable (AR424I) / Redundant Controller (AR424IR)	
COOLING FAN	1.5" Ball Bearing x3	2" Ball Bearing x2	3" Ball Bearing x4	3" Ball Bearing x4	
POWER SUPPLY	200W (100V-240V)	450W (100V-240V)	500W x2 Redundant	500W x3 Redundant	
CONTROL INTERFACE	Web, Serial Port, SSH		LCD, Web, Serial Port, SSH		
STATUS INDICATORS	Fan, Temperature, Power, HDD LEDs		Fan, Temperature, Power, HDD LEDs		
DIMENSIONS (IN)	19.0(W) x 21.0(D) x 1.7(H)	19.0(W) x 23.0(D) x 3.5(H)	19.0(W) x 20.5(D) x 5.5(H)	19.0(W) x 20.5(D) x 7.0(H)	
WEIGHT (LB)	15.4	42.0	44.0	50.0	
SAFETY REGULATIONS	CE, FCC, UL, RoHS		CE, FCC, UL, RoHS		
LIMITED WARRANTY	3 Years		3 Years		





SERIES	ACCURAIID			ACCUSTOR
MODEL	AR212X6(R) / AR212F8(R)	AR316X6(R) / AR316F8(R)	AR424X6(R) / AR424F8(R)	AS424X6S / AS424X6R*
PHOTO				
FORM FACTOR	2U 12-Bay Rackmount	3U 16-Bay Rackmount	4U 24-Bay Rackmount	4U 24-Bay Rackmount
HARD DRIVE TRAYS	Hot-Swappable 3.5" x12	Hot-Swappable 3.5" x16	Hot-Swappable 3.5" x24	Hot-Swappable 3.5" x24
MAXIMUM CAPACITY	48TB	64TB	96TB	96TB
DRIVE INTERFACE	SAS / SATA			SAS / SATA
HOST INTERFACE	Mini-SAS (SAS) x2 / x4 8G Fibre Channel x4 / x8			Mini-SAS 6G (SAS Expander)
RAID LEVEL	0, 1, 0+1, 3, 5, 6, 30, 50, 60, JBOD			JBOD (RAID Supported Via RAID Controller)
EXPANSION PORTS	Mini-SAS (Up to 7 JBOD Units)			Mini-SAS (Up to 7 JBOD Units)
HOT-SPARE	Yes			Via RAID Controller
REDUNDANT CONTROLLER	Yes (AR212X6R, AR212F8R, AR316X6R, AR316F8R, AR424X6R, AR424F8R)			Yes (AS424X6R)
COOLING FAN	3" Ball Bearing x2			3" Ball Bearing x2
POWER SUPPLY	500W x2 Redundant		500W x3 Redundant	500W x3 Redundant
CONTROL INTERFACE	LCD Panel, RS232, Web			Via RAID Controller
STATUS INDICATORS	Fan, Temperature, Power, HDD LEDs			Fan, Temperature, Power, HDD LEDs
DIMENSIONS (IN)	19.0(W) x 21.0(D) x 3.5(H)	19.0(W) x 21.0(D) x 5.5(H)	19.0(W) x 21.0(D) x 7.0(H)	19.0(W) x 21.0(D) x 7.0(H)
WEIGHT (LB)	38.0	47.0	80.0	80.0
SAFETY REGULATIONS	CE, FCC, UL, RoHS			CE, FCC, UL, RoHS
LIMITED WARRANTY	3 Years			3 Years

\*Also available in 2U 12-Bay and 3U 16-Bay

SERIES	ACCUNAS			NEXENTA
MODEL	AN2L+	AN4L+	AN5L+	NX212L+B / NX212L+BG
PHOTO				
FORM FACTOR	2-Bay Tower	4-Bay Tower	5-Bay Tower	2U 12-Bay Rackmount
HARD DRIVE TRAYS	Hot-Swappable 3.5" x2	Hot-Swappable 3.5" x4	Hot-Swappable 3.5" x5	Hot-Swappable 3.5" / 2.5" x12
MAXIMUM CAPACITY	8TB	16TB	20TB	48TB/Unlimited Connecting to JBOD
DRIVE INTERFACE	SATA			SAS / SATA
HOST INTERFACE	Gigabit Ethernet x1	Gigabit Ethernet x2		GbE x2 (w /10G Option)
RAID LEVEL	0, 1, JBOD	0, 1, 1+0, 5, 6		Mirror, Strip, RAID Z / Z2 / Z3
PROCESSOR	Marvell 6702	Atom D510	Atom D525	Intel Xeon Quad-core x2
MEMORY	256 MB	1GB DDR-2	1GB DDR-3	24GB DDR-3, up to 288GB
SUPPORTED PROTOCOL	CIFS, AFP	CIFS / ADS, AFP, NFS, iSCSI		CIFS, NFS, iSCSI, FC Target
HOT-SPARE	N/A	Yes		Yes
AUTO REBUILDING	N/A	Yes		Yes
COOLING FAN	1.5" Ball Bearing	4" Ball Bearing		5" Axial Cooling Fans
POWER SUPPLY	60W Power Adapter	200W (100V-230V)	400W (100V-230V)	750W 1+1 Redundant
CONTROL INTERFACE	Web Browser			Web Browser
STATUS INDICATORS	Power, HDD, LEDs			Power, HDD, LEDs
DIMENSIONS (IN)	3.7(W) x 8.5(D) x 5.6(H)	8.5(W) x 12.5(D) x 8.0(H)	12(W) x 8.0(D) x 8.5(H)	19.0(W) x 28.0(D) x 3.5(H)
WEIGHT (LB)	5.0	13.0	13.0	57
SAFETY REGULATIONS	CE, FCC, UL, RoHS			CE, FCC, UL, RoHS
LIMITED WARRANTY	1 Year			3 Years

SERIES	ELITENAS			
MODEL	EN104L+(B) / EN104L+(B)XE	EN208L+BXE / EN208W+BXE	EN316L+BXE / EN316W+BXE	EN872L+BXE / EN872W+BXE
PHOTO				
FORM FACTOR	1U 4-Bay Rackmount	2U 8-Bay Rackmount	3U 16-Bay Rackmount	8U 72-Bay Rackmount
HARD DRIVE TRAYS	Hot-Swappable 3.5" x4	Hot-Swappable 3.5" x8	Hot-Swappable 3.5" x16	Hot-Swappable 3.5" x72
MAXIMUM CAPACITY	16TB	32TB	64TB	288TB
DRIVE INTERFACE	SATA	SATA (w /SAS Option)	SAS / SATA	SAS / SATA
HOST INTERFACE	Gigabit Ethernet x2	GbE x2 (w /10G Option)	GbE x2 (w /10G Option)	GbE x4 (w /10G Option)
PROCESSOR	Intel ATOM / Intel Dual Core	Intel Dual Core CPU	Intel Xeon Quad-core CPU	Intel Xeon Quad-core CPU x2
MEMORY	1GB DDR-2 (EN104L+(B)) / 2GB DDR-2 (EN104L+(B)XE)	2GB DDR 2 ECC Memory Upgradeable to 4GB	4GB DDR-3 ECC Memory Triple Channel Mode	8GB DDR-3 ECC Memory Triple Channel mode
RAID LEVEL	0, 1, 1+0, 5, 6	0, 1, 1+0, 5, 6	0, 1, 1+0, 3, 5, 6, 30,50,60	0, 1, 1+0, 3, 5, 6, 30,50,60
EXPANSION PORTS	USB 2.0 x2	USB 2.0 x2 (Mini-SAS Option)	Mini-SAS x1	Mini-SAS x3
OPERATING SYSTEM	Linux	Linux/ Win Storage Server '08	Linux/ Win Storage Server '08	Linux/ Win Storage Server '08
POWER SUPPLY	220W (100V-240V)	380W 1+1 Redundant	650W 2+1 Redundant	1500W 2+1 Redundant
CONTROL INTERFACE	Web GUI Mangement			
STATUS INDICATORS	HDD & Power LEDs			
DIMENSIONS (IN)	19.0(W) x 21.0(D) x 1.7(H)	19.0(W) x 28.0(D) x 3.5(H)	19.0(W) x 28.0(D) x 5.5(H)	19.0(W) x 31.0(D) x 14.0(H)
WEIGHT (LB)	18.0	42.0	75.0	150.0
SAFETY REGULATIONS	CE, FCC, UL, RoHS			
LIMITED WARRANTY	3 Years			
	Also available in 4U 24-Bay and 8U 48-Bay			

SERIES	TOWERRAID+			
MODEL	TR4M+ / TR4M+B	TR5M+ / TR5M+B	TR8M+ / TR8M+B	TR4X+P / TR4X+P
PHOTO				
FORM FACTOR	4-Bay Tower	5-Bay Tower	8-Bay Tower	4-Bay Tower
HARD DRIVE TRAYS	Trayless	Hot-Swappable 3.5" x5	Hot-Swappable 3.5" x8	Trayless
MAXIMUM CAPACITY	16TB	20TB	32TB	16TB
DRIVE INTERFACE	SATA			SAS / SATA
HOST INTERFACE	eSATA (Port Multiplier) x1	eSATA (Port Multiplier) x1	eSATA (Port Multiplier) x2	Mini-SAS x1
RAID LEVEL	0, 1, 10, 5, 5+Spare, Spanning and JBOD (Via Bundled RR622 Card)	0, 1, 10, 5, 5+Spare, Spanning and JBOD (Via Bundled RR622 Card)	0, 1, 10, 5, 5+Spare, Spanning and JBOD (Via Bundled RR622 Card)	0, 1, 10, 5, 5+Spare Spanning and JBOD (Via Bundled RR2711 Card)
EXPANSION PORTS	N/A			
HOT-SPARE	Yes			
AUTO REBUILDING	Yes			
COOLING FAN	3.15" Ball Bearing	4.7" Ball Bearing	4.7" Ball Bearing	3.15" Ball Bearing
POWER SUPPLY	150W (115V-230V)	220W (103V-253V)	250W (90V-264V)	150W (115V-230V)
CONTROL INTERFACE	Web Based GUI			
STATUS INDICATORS	Hard Drive & Power LEDs			
DIMENSIONS (IN)	5.3(W) x 10.0(D) x 7.1(H)	6.0(W) x 11.0(D) x 8.3(H)	5.9(W) x 13.4(D) x 13.4(H)	5.3(W) x 10.0(D) x 7.1(H)
WEIGHT (LB)	5.9	9.3	13.0	5.9
SAFETY REGULATIONS	CE, FCC, UL, RoHS			
LIMITED WARRANTY	1 Year			

SERIES	TOWERRAID+			
MODEL	TR4UT+ / TR4UT+B	TR5UT+ / TR5UT+B	TR8UT+ / TR8UT+B	TR8X+P / TR8X+BP
PHOTO				
FORM FACTOR	4-Bay Tower	5-Bay Tower	8-Bay Tower	8-Bay Tower
HARD DRIVE TRAYS	Trayless	Hot-Swappable 3.5" x5	Hot-Swappable 3.5"	Hot-Swappable 3.5" x8
MAXIMUM CAPACITY	16TB	20TB	32TB	32TB
DRIVE INTERFACE	SATA			SAS / SATA
HOST INTERFACE	USB 3.0 x1 & eSATA x1	USB 3.0 x1 & eSATA x1	JBOD, USB 3.0 x1, & eSATA x1	Mini-SAS x2
RAID LEVEL	0, 1, 10, 3, 5, Clone (N-way Mirror) and JBOD (Hardware RAID)	0, 1, 10, 3, 5, Clone (N-way Mirror) and JBOD (Hardware RAID)	00, 30, 50, and JBOD	0, 1, 1+0, 5, and JBOD with Hot Spare (Via Bundled RR2722 Card)
EXPANSION PORTS	N/A			
HOT-SPARE	Yes			
AUTO REBUILDING	Yes			
COOLING FAN	3.15" Ball Bearing	4.7" Ball Bearing	4.7" Ball Bearing	4.7" Ball Bearing
POWER SUPPLY	150W (115V-230V)	220W (103V-253V)	250W (90V-264V)	250W (90V-264V)
CONTROL INTERFACE	RAID Switch Monitoring Software	RAID Switch Monitoring Software	RAID Switch	Web Based GUI
STATUS INDICATORS	HDD Status & Power LEDs			
DIMENSIONS (IN)	5.3(W) x 10.0(D) x 7.1(H)	6.0(W) x 11.0(D) x 8.3(H)	5.9(W) x 13.4(D) x 13.4(H)	5.9(W) x 13.4(D) x 13.4(H)
WEIGHT (LB)	5.9	9.3	13.0	13.0
SAFETY REGULATIONS	CE, FCC, UL, RoHS			
LIMITED WARRANTY	1 Year			

1-800-980-1988    SANSDIGITAL.COM



**United States Headquarter:**  
783 PHILLIPS DRIVE  
CITY OF INDUSTRY, CA 91748

**Taiwan:**  
9F, NO. 36 JILIN ROAD  
TAIPEI 10424, TAIWAN

Copyright © 2012 Sans Digital. All rights reserved. Sans Digital and the Sans Digital logo are registered trademarks of Sans Digital. Other products and company names mentioned herein may be trademarks of their respective companies. No part of this design may be reproduced in any form without the expressed written consent of Sans Digital. Information presented is subject to change without notice. Under no circumstances will Sans Digital be held responsible for direct, indirect, special, incidental, or consequential damages arising from the use or inability to use the product or documentation.